

AF

REFRIGERATED CABINETS



GENERAL FEATURES

WORKING TEMPERATURE:

+4°C or -20°C

TEMPERATURE RANGE:

0°C/+10°C or -10°C/-20°C

CONTROL PANEL:

Electronic digital regulator with red luminous display, complete with min end max temperature allarms with RS 485 interface.

FRAME:

totally metallic with zinc-plasticized steel sheet of icy white and light blue colour. Drainage on the bottom for the evacuation of liquids, adjustable feet..

INSULATION:

CFC FREE realized by foamed polyurethane. The minimun thickness is 55 mm.

DOOR:

with anticondense resistance on door frame. Provided with special magnetic rubber washer for perfect closing. The door has opening on the right and on the left. The standard is on the right.

REFRIGERATING PLANT:

CFC FREE hermetic type with air condensation.

TECHNICAL FEATURES

Code	Model	CAP.	RIP.	Doors	Ext Dimension	Power Volt	Watt	Weight
01010121	AF 400/1P	400	2	1	700X640X1800h	220/1/50 HZ	250	60
01010122	AF 400/1PV	400	2	1	700X640X1800h	220/1/50 HZ	250	70
01010123	AF 500/1P	550	2	1	730X700X2090h	220/1/50 HZ	350	100
01010124	AF 500/1PV	550	2	1	730X700X2090h	220/1/50 HZ	350	110
01010127	AF 700/1P	700	3	1	730X830X2090h	220/1/50 HZ	387	110
01010128	AF 700/1PV	700	3	1	730X830X2090h	220/1/50 HZ	387	120
01010131	AF 700/2P	700	2	2	730X830X2090h	220/1/50 HZ	387	115
01010134	AF 1000/2P	1000	4	2	1460X700X2090h	220/1/50 HZ	500	154
01010135	AF 1000/2PV	1000	4	2	1460X700X2090h	220/1/50 HZ	500	164
01010137	AF 1500/2P	1500	6	2	1460X790X2090h	220/1/50 HZ	550	177
01010140	AF 1500/2PV	1500	6	2	1460X790X2090h	220/1/50 HZ	550	187
01010142	AF 2300/3P	2100	9	3	2100X830X2090h	220/1/50 HZ	740	270
01010143	AF 2300/4P	2100	9	4	2100X830X2090h	220/1/50 HZ	740	270
01010144	AF 700/2TE	300+300	2	2	730X830X2090h	220/1/50 HZ	800	150
01010145	AF 1500/2TE	650+650	6	2	1460X830X2090h	220/1/50 HZ	1120	190

Execution in accordance with the norms CEI 66/5.

* NOTE: the AF 500 and 1000 are totally in aluminium

* With the added suffix BT the closet to temperature -20°C execution AF 400 and 2300 will be achieved

STANDARD ACCESSORIES

- 09920195 Digital display for the regulation and control of temperature with red light displays plus min. and max. temperature alarms.
- 09910171 Internal lighting
- 09910172 Internal ventilation
- 09910173 Safety Key-lock
- 09910125 Internal shelves
- 00000000 Automatic electronic defrosting
- 09910174 Adjustable feet

OPTIONAL ACCESSORIES

09940193 Weekly Graphic Recorder
09910125 Adjustable internal drawers
09910131 Internal box inox 304 with drained bottom better to allow the circulation of the air and the elimination of liquids, with nylon wheels, adjustable in height.
09910136 Inox frame
09910142 No electric contacts
09910147 Hole diam. 35 mm. with rubber plug.
09910149 All glass door
09910151 Remotisation of the alarm
00000000 Special voltage

Characteristics and data can be modified without forewarning

C.T.I. s.r.l.

Climatic Technologies Industry

20812 LIMBIATE (MB) MILANO ITALY Via Monte Rosa, 27 Capannone 17

Tel. +390296460000 Fax +390296461445 e-mail: info@ctisrl.eu